

SNS LLRF System Review



Beam Dynamics Aspects

D. Jeon, H. Takeda, J. Stovall, K. Crandall





October 8, 2002

ASD


When the LLRF control errors are relaxed for the entire Linac to $\pm 1^\circ$ and $\pm 1\%$ (phase and amplitude).



- beam E, ϕ centroid jitter at the end of SCL




Beam centroid energy jitter after passing through the energy corrector cavity



0.5° and 0.5% phase and amplitude jitter of LLRF

98.7% are within ± 0.2 MeV



LLRF control errors are relaxed to 1.0° and 1.0% for entire linac


89.9% are within ± 0.2 MeV

Transverse rms emittances grow 10% when relaxing LLRF control errors




10 linac runs

$0.5^\circ, 0.5\%$







$1.0^\circ, 1.0\%$




When the LLRF control errors are relaxed only for DTL



At the end of the SCL




Beam centroid energy jitter after passing through the energy corrector cavity



0.5° and 0.5% phase and amplitude jitter of LLRF

98.7% are within ± 0.2 MeV







LLRF control errors are relaxed to 1.0° and 1.0% only for DTL

95.3% are within ± 0.2 MeV


When the LLRF control errors are relaxed only for DTL and CCL



At the end of SCL




Beam centroid energy jitter after passing through the energy corrector cavity



0.5° and 0.5% phase and amplitude jitter of LLRF

98.7% are within ± 0.2 MeV







LLRF control errors are relaxed to 1.0° and 1.0% for DTL/CCL

93.7% are within ± 0.2 MeV

Simulated centroid energy and phase jitter at the DTL end with $\pm 1^\circ$ and $\pm 1\%$ rf error







$\pm 4.5^\circ$ and $\pm 0.01\text{MeV}$ injection beam jitter are assumed



Simulated centroid energy and phase jitter at the CCL end with $\pm 1^\circ$ and $\pm 1\%$ rf error



$\pm 4.5^\circ$ and $\pm 0.01\text{MeV}$ injection beam jitter are assumed



- Commissioning DTL and CCL with $\pm 1^\circ$ and $\pm 1\%$ rf error seems doable.
- Work in progress
- Multiparticle tracking studies using Parmila are under way.