



PMC A DIVISION OF ROCKBESTOS-SURPRENANT CABLE CORPORATION
 680 HAYWARD STREET, MANCHESTER, NH 03103 (603) 622-3500
 SPECIALIZING IN WIRE & CABLE FOR THE SENSOR INDUSTRY FAX (800) 639-5701

QUOTE SPECIFICATION

Quote Number: NA-083
 PMC Part Number: TX-201PC/PC031-22U
 Customer Drawing Number: None supplied

This specification covers a one pair, 22 AWG solid, type T, extension grade, standard limits of error, PVC insulated and jacketed, tape shielded cable, rated to 221°F. This cable is UL Listed Type PLTC, 300V.

Conductor:

Size: 22 AWG
 Nominal OD: 0.025"
 Positive leg: TPX thermoelement, Cu
 Negative leg: TNX thermoelement, CuNi

Insulation:

Material: PVC 105°C
 Nominal wall: 0.015"
 Nominal OD: 0.055"
 Color code: (+) Blue; (-) Red

Cable:

Nominal lay: 1.50" left hand
 Drain wire: 22 AWG stranded tinned copper
 Shield: Aluminized polyester tape, minimum 25% lap
 Nominal OD: 0.114"

Jacket:

Material: PVC 105°C
 Nominal wall: 0.040"
 Nominal OD: 0.194"
 Color code: Blue
 Print legend: In accordance with UL Type PLTC

NOTE: This document is company confidential and cannot be reproduced without the expressed written consent of PMC, a division of R-SCC.

PMC APPROVAL

Rev	Revision	Date	By	Approved
A	Initial Release	4/10/02	DMC	

CUSTOMER APPROVAL

Date	Approved By (Printed)	Signature

