
HIGH FLUX ISOTOPE REACTOR

NSTRUMENT



POLARIZED TRIPLE-AXIS SPECTROMETER

The HB-1 Polarized Triple-Axis Spectrometer is designed primarily for the study of excitations in crystalline solids at intermediate energies. Thanks to the vertical beam focusing and the very high time-averaged flux at HFIR, its geometry is optimal for investigating small samples and weak scattering in specific areas of energy-momentum



space. The sample goniometers and a full software implementation of the three-dimensional sample orientation matrix allow measurements outside the traditional singlescattering plane. The unique capability of HB-1 is the polarized configuration for studies of excitations, phase transitions, structures, and density distributions in magnetic materials.

APPLICATIONS

- Spin waves in ordered magnetic materials
- Exotic excitations in low-dimensional, molecular, itinerate, and other "quantum" magnets
- Spin and lattice excitations in high-T_c superconductivity, colossal magnetoresistance materials, and multiferroic systems
- Spin density distributions in magnetic compounds
- Detailed spin structure, including chirality
- Phonon dispersion curves in alloys and phonon-driven phase transitions

SPECIFICATIONS

Beam spectrum	Thermal
Monochro- mators	Unpolarized vertical focus PG(002)
	Polarized Vertical Focus Heusler(111)
Analyzers	Unpolarized fixed verti- cal focus PG(002), Be(101), Si(111) Polarized Heusler (111)
Monochro- mator angle	$2\Theta_{\rm M} = 14 \text{ to}$ 75°
Sample angle	±180°
Scattering angle	–90 to 120°
Analyzer angle	–40 to 140°
Collimations (FWHM)	Premonochromator: 15', 30', 48'
	Monochromator-sample: 20', 40', 60', 80'
	Sample-ana- lyzer: 20', 40', 60', 80'
	Analyzer-de- tector: 20', 70', 90', 120', 210', 240'
Detector	Single ³ He gas counter
Resolution (elastic)	5–10% Ei (adjustable with collimators)

Status: Available to users



Instrument Scientist: Masaaki Matsuda, matsudam@ornl.gov, 865.574.6580 neutrons.ornl.gov/hb1

